

TEUPEN[®]

...access redefined

LE025Tplus

Working height:
25.20 m

Lateral reach:
15.00 m

Machine width:
1.58 m


Machine height:
1.98 m

Weight:
3,760 kg

- Compact design, travels through a double door
- Light, low surface load for use on sensitive flooring
- Smooth, proportional electro-hydraulic controls
- Reliable and comprehensive safety control system
- Hydrostatic platform leveling
- Automatic, multi-position & self leveling outriggers
- Hydraulically adjustable tracks
- Fuzzy IV control logic with interactive user display
- Dual Power (Diesel and A/C electric) for indoor and outdoor use

[www.TEUPEN.com](http://www.teupen.com)

Teupen Maschinenbau GmbH
phone +49 2562 8161 0
fax +49 2562 8161 888
mail@teupen.com



Compact tracked boom lift - LE025Tplus

Accessing jobsites at height safely and efficiently often poses unsolvable challenges to building managers. Narrow entrances, confined work areas and floor load restrictions can make the use of standard aerial lifts impossible.

With the LEO Series[®], Teupen offers the original tracked aerial lift in a complete range for demanding indoor and rugged outdoor applications from 13 to outstanding 50 metres working height.



LEOSERIES



LEO25Tplus



On the powerful track drive the LEO25Tplus can be maneuvered precisely. It even allows the machine climb steep slopes and stairs.



An interactive display in the control panel shows all available boom functions, safety information and allows error analysis.



The automatic outrigger system levels out height differences perfectly. Additionally, three different outrigger setup positions are available.



The LEO25Tplus features a 180° rotatable basket for more versatility when positioning the basket into tight spots, working alongside façades or in trees.

Top features:

- Compact** – Fits through standard double door
- Light** – Low ground pressure to protect sensitive surfaces
- Versatile** – Highest maneuverability on white rubber tracks
- Easy** – Automatic self-levelling stabilisers
- Simple** – Color coded & well-arranged control panel
- Power** – Multiple power sources for indoor and outdoor work

Overview: LEO Series models from 23 to 36 metres working height

Model	LEO23GT	LEO25T	LEO25Tplus	LEO30T	LEO36T
Working height	23,00 m	25,00 m	25,20 m	30,00 m	35,50 m
Outreach	11,20 m	12,50 m	15,00 m	14,00 m	13,90 m
Weight	2990 kg	2980 kg	3760 kg	4225 kg	4850 kg
Width	0,98 m	1,78 m	1,58 m	1,58 m	1,58 m
Movable Jib	-	-	-	✓	✓
Adjustable tracks	✓	✓	✓	✓	✓
Rotatable basket	✓	✓	✓	✓	✓

LEO = Model, Number = Metric Working height, G = Articulated, T = Telescopic